

INTRODUCING

G-Series P25 Voice Paging Solutions

G4 Industry First P25 Voice Pager

Supports

P25 Conventional
P25 Phase I & Phase II Trunking

Available In

700 - 800 MHz



G5 Industry First Dual Band P25 Voice Pager

Supports

Analog 2-Tone Conventional
P25 Conventional
P25 Phase I & Phase II Trunking

Available In

VHF & 700 - 800 MHz
UHF & 700 - 800 MHz



Features Included:

Up to 256 Channels
IP67 RATING - Waterproof & Dustproof
Submersible up to 3ft/30 Minutes
High Impact Resistant Color Screen
Rugged Housing

Custom Wav Files Alerts
Bluetooth
32 Minutes Voice Storage
32 Minutes Voice Memo
2 Year Standard Warranty (Optional 3+)

Key Features

G4 Model Includes:

- Accommodates Multiple P25 Trunked and P25 Conventional Systems
- Supports the 800MHz Analog Frequencies
- Supports up to 256 Control Channels/per Trunked System
- Supports Full Spectrum Scan for P25 Trunked System
- Supports Multiple TGIDs for Monitoring and Alerting
- Supports Priority TGID Scan
- Supports Multiselect for Efficient Use of Traffic Channels
- Allows for Customized Alerts using WAV/MP3 Files
- Alerting Options based on a Selector Knob Setting



G5 Model Has All of the Above Features Plus:

- Each Band Supports P25 Trunking, P25 Conventional, Conventional Channel Monitoring and 2-Tone Decoding
- Full 2-Tone Function Mode Support (Selective Call, Monitor, Scan Options)
- Supports Multiple 2-Tone Codes per Frequency

Models	Frequency Range
G4 P25 Voice Pager - 700 - 800 MHz	763-776 MHz, 851-870 MHz
G5 Dual Band Voice Pager- VHF & 700 - 800 MHz	VHF: 136-174 MHz / 763-776 MHz, 851-870 MHz
G5 Dual Band Voice Pager- UHF & 700 - 800 MHz	UHF A: 330 - 400 MHz / 763 - 776 MHz, 851 - 870 MHz UHF B: 380 - 430 MHz / 763 - 776 MHz, 851 - 870 MHz UHF C: 400 - 470 MHz / 763 - 776 MHz, 851 - 870 MHz UHF D: 450 - 512 MHz / 763 - 776 MHz, 851 - 870 MHz

Both Models Feature:

- Up to 256 Channels*
- Custom WAV File Alerts*
- IP67 RATING Waterproof & Dustproof*
- Out of Range Alert*
- Submersible up to 3 ft for 30 Minutes*
- Bluetooth*
- High Impact Resistant Color Screen*
- 32 Minutes Voice Storage*
- Rugged Housing*
- 32 Minutes Voice Memo*
- 2 Year Standard Warranty / 3 Year Addition Available*

Technical Specifications

Sensitivity	-116dBm	Ingress Protection Rating	IP67- Waterproof/Dustproof
Sensitivity/12dB SINAD	6 uV/M	UL	Class I, Div. II
Frequency Stability	+1ppm	FCC	FCC Part 15
Adjacent Channel Selectivity	>60dB	MIL-STD	810E, Proc1 for Driving Rain
Spurious	>70dB	Channel Spacing	25kHz/12.5KHz/6.25KHz
Image Rejection	>70dB	Battery	2800 mAH Lithium Ion
Audio Output Linear	>300mW	Weight (w/out Battery)	<220g
Audio Distortion	<2%	Size (mm)	102 x 61 x 31.5
Speech SPL (at 12 inches)	96dB +3dB/-2dB	Temperature Range	-4°F ~ +104°F
Alert SPL (at 12 inches)	96dB +3dB/-2dB		